

# MFT SERIES

## WATER SOFTENERS

Water Control “MFT” Series softeners feature 1½” service connections, heavy duty electronic (dual-service) control valves, two (2) non-corrosive high-strength fiberglass mineral tanks, and long-lasting synthetic cation resin. This series is perfectly designed for apartments, hotels, commercial laundry, schools, hospitals, and other applications where 24 hour soft water is required. “MFT” Series softeners feature a dual tank, alternating system, allowing one tank to be in service at all times. Available options include steel resin tanks and specialty filtration systems.



### SPECIFICATIONS

Model Series Number	Exchange Capacity* (grains)			Cv	Flow Rate (gpm)			Pipe Size (inches)		Back Wash (gpm)	Resin (cu ft)	Brine Tank Capacity (lbs)	Regen. Time (min)	Tank Size (in)		Approx. Ship Weight (lbs)
	Min <sup>1</sup>	Mid <sup>2</sup>	Max <sup>3</sup>		7 psid	Cont. 15 psid	Peak 25 psid	Service	Drain					Resin	Salt	
MFT-90	63000	90000	96000	8.4	22	30	42	1 ½	1	5	3/tank	670	90	14 X 65	24 x 50	500
MFT-120	84000	120000	128000	9	24	33	45	1 ½	1	7	4/tank	640	92	16 X 65	24 x 50	520
MFT-150	105000	150000	160000	8.2	22	30	41	1 ½	1	7	5/tank	600	94	16 X 65	24 x 50	640
MFT-180	126000	180000	192000	10.2	27	40	51	1 ½	1	12	6/tank	590	90	21 X 62	24 x 50	675
MFT-210	147000	210000	224000	10	27	39	50	1 ½	1	12	7/tank	560	92	21 X 62	24 x 50	850
MFT-240	168000	240000	256000	11.2	30	42	56	1 ½	1	15	8/tank	525	94	24 X 72	24 x 50	1150
MFT-300	210000	300000	320000	10.8	29	40	54	1 ½	1	15	10/tank	490	96	24 X 72	24 x 50	1350

<sup>1</sup> Based on 6 lbs salt per cubic foot.

<sup>2</sup> Based on 10 lbs salt per cubic foot.

<sup>3</sup> Based on 15 lbs salt per cubic foot.

All “MFT” Series softeners utilize series 9500 controllers, pre-wired with 3-prong connectors, 120 VAC, 60 Hz, 5 Amps or less (G.F.I. wall outlet is required).

*\* Exchange capacity based on treating water with 10 gpg total hardness as CaCo<sub>3</sub> and 400 ppm total dissolved solids. Capacities may vary with different influent water characteristics and other factors. Due to varying water conditions, tank sizes and water pressures, the above should only be used as a guideline.*

**WITH OVER 45 YEARS OF EXPERIENCE IN THE WATER CONDITIONING AND PLUMBING INDUSTRIES,** WATER CONTROL CAN DESIGN AND MANUFACTURE EQUIPMENT FOR VIRTUALLY ANY APPLICATION. WE OFFER A COMPLETE MENU OF SERVICES, INCLUDING WATER TESTING, SYSTEM SIZING, BIM MODELING (REVIT™), DELIVERY, SETUP, STARTUP, AND AFTER-MARKET SERVICE PLANS. WE MAINTAIN A UNIQUE FOCUS ON MECHANICAL ENGINEERS, CONTRACTORS, AND THE PLUMBING INDUSTRY. DEPEND ON US TO PROVIDE QUALITY, INNOVATIVE SOLUTIONS FOR ALL YOUR COMMERCIAL WATER CONDITIONING NEEDS.

## HOW TO SPECIFY “MFT” SERIES SOFTENERS:

### ORDER CODE:



### MODEL (from other side)

### SYSTEM SIZE

Two Tank (Alternating): **TWIN - ALT**

### Additional Options: (check options below)

- Steel Tank(s) (optional ASME Rating)
- Accu-Pipe Skid-Mounted System (pre-plumbed, pre-wired system, mounted on heavy-duty skid)
- Accu-Pipe LS: Same as Accu-Pipe System, less skid base (piping/wiring only)
- Brine Silo (large volume salt storage / brine generation & delivery system)
- Salt Sock and Access Door (lockable) for blow-in salt delivery

### Specialty Filter Options: (check options below)

- Carbon
- Tannin
- Acid Neutralizer (Calcite)
- Dealkalizer
- Additional media options available, call for details

*\*For a detailed, model-specific specification, please contact Water Control Corporation. Detailed drawings also available upon request (CAD™ or Revit™).*

*Water softening system requires a minimum inlet water pressure of 30 psig and maximum of 120 psig. If storage tank is subject to vacuum, an adequate vacuum relief valve must be properly installed. Tank warranty is void if subjected to vacuum. Feed water temperature shall be between 40°F and 100°F. Each control valve requires a 120 volt GFCI wall outlet.*

We have team members throughout the US and Canada who are ready to serve you.

To get started, please talk with your local sales representative, or contact our Technical Support Department: 1-866-405-1268 or [techsupport@watercontrolinc.com](mailto:techsupport@watercontrolinc.com)

Water Control Corporation  
7150 143rd Ave NW • Ramsey, MN 55303  
Phone: 763-427-9638 • Fax: 763-427-5665  
[www.watercontrolinc.com](http://www.watercontrolinc.com)



© Water Control Corporation 0317

WATER CONTROL