DAKOTAH®

Residential Water Softening System



An Employee-Owned Company







DAKOTAH water softeners are built to last by Water Control Corporation, a leader in residential and commercial water treatment technologies.

All models feature digital, programmable valves, high flow capacities, and standard 1" pipe connections (optional 3/4" available upon request).

- 3 year valve warranty*
- 5 year tank warranty*

NOTE

- This equipment is not intended to be used for treating water that is microbiologically unsafe or of unknown quality without disinfection before or after the system.
- This system and installation must comply with local and state laws and regulations.
- This equipment conforms to NSF/ANSI 44 for specific performance claims as verified and sunstantiated by test data.

*See official warranty for details

Specifications	Cabinet Models		Two-Tank Models			
DAKOTAH SERIES	DS24	DS32	DST24	DST32	DST48	DST60
Grain Capacity Removal	24,000	32,000	24,000	32,000	48,000	60,000
Lbs Salt / Regeneration	9	12	9	12	18	24
Service Flow Rate (GPM)	10	11	10	11	13	14
Max Flow Rate (GPM)	14	16	14	16	17	21
Backwash Rate (GPM)	1.2	1.5	1.2	1.5	3.5	3.5
Brine Tank Salt Capacity (Lbs)	200	200	300	300	300	300
Max Iron Capacity (PPM)	2	2	2	2	2	2
Mineral Tank Dimensions (Inches)	8 X 35	9 X 35	7 X 44	8 X 44	10 X 47	10 X 54
Brine Tank Dimensions (Inches)	14 X 20	14 X 20	18 X 33	18 X 33	18 X 33	18 X 33
Overall Height	44"	44"	52"	52"	55.5"	62"
Inlet / Outlet Pipe Size*	1"	1"	1"	1"	1"	1"
Inlet / Outlet Height (to center)	39"	39"	46.5"	46.5"	50.25"	57"
Pipe Centers	3"	3"	3"	3"	3"	3"
Approx. Shipping Weight (Lbs)	52	57	57	62	86	113
*Other sizes available. Call for details.						

Water Control Corporation 7150 143rd Ave NW Ramsey, MN 55303 Phone: 763-427-9638 www.watercontrolinc.com

WR-DAKTH

© Water Control Corporation 0322

