

MF SERIES

WATER SOFTENERS

WCC's "MF" Series softeners feature 1½" service connections, heavy duty electronic control valves, high-strength fiberglass-reinforced mineral tanks, and long-lasting synthetic cation resin. This series is perfectly designed for apartments, commercial laundry, schools, hospitals, industrial facilities, and cooling towers. Available options include steel resin tanks, brine reclamation, and Accu-Pipe skid systems.



SPECIFICATIONS

Model Series Number	Exchange Capacity* (grains)			Valve Size (in)	Cv	Flow Rate (GPM)			Pipe Size (in)		Back Wash (GPM)	Resin (cu.ft.)	Brine Tank Capacity (lbs)	Regen. Time (min)	Tank Size (in)		Approx. Ship Weight (lbs)
	Min ¹	Mid ²	Max ³			7 psid	Cont. 15 psid	Peak 25 psid	Service	Drain					Resin	Salt	
MF-48	36800	43200	48000	1 ½	8.3	22	32	42	1.5	¾	4	1.6	225	90	12 X 52	18 X 33	150
MF-60	46000	54000	60000	1 ½	8	18	28	40	1.5	¾	3	2	225	90	12 X 52	18 X 33	175
MF-90	69000	81000	90000	1 ½	8.4	22	30	42	1.5	¾	5	3	650	90	14 X 65	24 X 50	300
MF-120	92000	108000	120000	1 ½	9	24	33	45	1.5	¾	7	4	650	92	16 X 65	24 X 50	375
MF-150	115000	135000	150000	1 ½	8.2	22	30	41	1.5	¾	5	5	625	94	16 X 65	24 X 50	425
MF-150X	115000	135000	150000	1 ½	10.3	28	38	52	1.5	1	8	5	625	96	18 X 65	24 X 50	450
MF-180	138000	162000	180000	1 ½	10.2	27	40	51	1.5	1	12	6	600	90	21 X 62	24 X 50	600
MF-210	161000	189000	210000	1 ½	10.4	28	40	52	1.5	1	10	7	575	92	21 X 62	24 X 50	650
MF-240	184000	216000	240000	1 ½	11.2	30	42	56	1.5	1	15	8	550	94	24 X 72	24 X 50	725
MF-300	230000	270000	300000	1 ½	10.8	29	40	54	1.5	1	12	10	500	96	24 X 72	24 X 50	825

¹ Based on 7 lbs salt per cubic foot.

² Based on 10 lbs salt per cubic foot.

³ Based on 13 lbs salt per cubic foot.

All "MF" Series softeners utilize series 2850 NXT2 controllers.

* Exchange capacity based on treating water with 10 gpg total hardness as CaCo3 and 400 ppm total dissolved solids. Capacities may vary with different influent water characteristics and other factors. Due to varying water conditions, tank sizes and water pressures, the above should only be used as a guideline.




ADVANCED CONTROLLER

- Real-time diagnostics
Flow rates, totalizer, capacity, avg. usage, alarm history, and more
- Remote input for forced regeneration and regeneration lockout
- 2 programmable relays for auxiliary equipment, BAS indication, remote alarms, etc.

WITH OVER 50 YEARS OF EXPERIENCE IN THE WATER CONDITIONING AND PLUMBING INDUSTRIES, WCC CAN DESIGN AND MANUFACTURE EQUIPMENT FOR VIRTUALLY ANY APPLICATION. WE OFFER A COMPLETE MENU OF SERVICES, INCLUDING WATER TESTING, SYSTEM SIZING, BIM MODELING (REVIT®), DELIVERY, SETUP, STARTUP, AND AFTER-MARKET SERVICE PLANS. WE MAINTAIN A UNIQUE FOCUS ON MECHANICAL ENGINEERS, CONTRACTORS, AND THE PLUMBING INDUSTRY. DEPEND ON US TO PROVIDE QUALITY, INNOVATIVE SOLUTIONS FOR ALL YOUR COMMERCIAL WATER CONDITIONING NEEDS.

HOW TO SPECIFY “MF” SERIES SOFTENERS:



ORDER CODE:

MODEL (from other side)

SYSTEM SIZE

Additional Options: (check options below)

- ☐ Brine Reclamation: Re-uses brine solution for significant salt savings (approx 30%)
- ☐ Steel Tank(s) (optional ASME Rating)
- ☐ Accu-Pipe Skid-Mounted System (pre-plumbed**, pre-wired system, mounted on heavy-duty powder-coated steel skid)
- ☐ Accu-Pipe LS: Same as Accu-Pipe System, less skid base (piping/wiring only)
- ☐ Brine Silo (large volume salt storage / brine generation & delivery system)
- ☐ Salt Sock and Access Door (lockable) for blow-in salt delivery

****** Standard piping is grooved, type L copper, other materials available.

For a detailed, model-specific specification, please contact WCC (Water Control Corporation). Detailed drawings also available upon request (CAD® or Revit®).

Water softening system requires a minimum inlet water pressure of 30 psig and maximum of 120 psig. If resin tank is subject to vacuum, an adequate vacuum relief valve must be properly installed. Tank warranty is void if subjected to vacuum. Feed water temperature shall be between 40°F and 100°F. Each control valve requires a 120 volt wall outlet (2-prong, 1.3FLA, 60Hz).



CONTACT YOUR LOCAL
SALES REPRESENTATIVE

To find your authorized WCC representative,
please visit: [www.watercontrolinc.com/
representative-locator/](http://www.watercontrolinc.com/representative-locator/).



VISIT US ONLINE

Go to www.watercontrolinc.com, where
you'll find detailed product specification
info and application design questionnaires.



SPEAK DIRECTLY WITH ONE OF
WCC'S DESIGN ENGINEERS

Call 1-866-405-1268 or email
techsupport@watercontrolinc.com.

We look forward to working with you!

Water Control Corporation
7150 143rd Ave NW • Ramsey, MN 55303
1-866-405-1268 • www.watercontrolinc.com

WC-MF © Water Control Corporation 0924

